



GENERAL MONITORS
Protection for life.

ARGC

Automatic Remote Gas Calibrator



Features

- Capable of being actuated electronically
- Easy to install
- Two-part design for gas application
- Checks integrity of the gas sensor diffusion path

Benefits

- When used with S4000CH, allows operators to calibrate detector via HART or Modbus
- No electrical wiring or connections
- Easy to calibrate sensor in remote locations
- Fail safe operation

Description

To verify the proper operation of a catalytic combustible gas sensor, it is necessary to periodically apply a gas of known concentration to the sensor. This is usually done manually at the site with gas supplied from a small lecture bottle. As the sensor reacts to the calibration gas, adjustments are made to the monitoring system to bring its calibration into agreement with the known concentration of gas.

At times, sensors are mounted in inaccessible locations, requiring expensive catwalks or scaffolding to reach them. The Automatic Remote Gas Calibrator (ARGC) allows the calibration gas to be applied to the catalytic bead sensor from easily accessible locations.

The ARGC is used for blocking ambient air and re-directing methane or other light hydrocarbon gases to the catalytic sensor for calibration or testing sensor accuracy. The ARGC tests or calibrates the General Monitors catalytic sensor with 50% LEL methane or other light hydrocarbon gas. The unit is capable of calibrating gases at wind velocities up to 50 mph.

Applications

- Hard-to-reach sensor locations
- Warehouses
- Drilling rigs
- Crude oil pumping stations
- Petrochemical plants
- Refineries
- Aircraft hangars



AUTOMATIC REMOTE GAS CALIBRATOR

System Specifications

Input Power:	24 VDC from S4000CH (ARGC only)
Electrical Classification:	Class I, Div 1, Groups B, C, and D; Class I, Zone 1, Group IIB + H2; T6, Ta = +75°C
Warranty:	Two years
Part Numbers:	80153-1 (RGC) 80154-1 (ARGC solenoid valve and hardware) 80155-1 (remote installation ARGC) 32547-1 (remote junction box with connecting board)

Environmental Specifications

Operating Temperature:	-40°F to 167°F (-40°C to 75°C)
Storage Temperature:	-40°F to 167°F (-40°C to 75°C)
Humidity:	5-95%, non-condensing
Air Velocity:	0 to 50 ±5 mph
Accuracy:	5% to 20% of full scale depending on angle of air flow
Response Time*:	T ₅₀ < 10 seconds, T ₉₀ < 30 seconds

Mechanical Specifications

Operating Pressure:	45 ±5 psi
Maximum Tubing Length:	200 ft for 1/8 inch tubing (OD) 100 ft for 1/4 inch tubing (OD)



RGC
(P/N 80153-1)



ARGC
(P/N 80153-1 & 80154-1)



ARGC with Junction Box
(P/N 80155-1)

* Response time of S4000CH assumes sample tubing is pressurized with calibration gas.

Specifications subject to change without notice.

Represented by:

General Monitors Worldwide



www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
Email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
Email: gmlhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
Email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road
#09-16 Mactech Building
Singapore 349307
Tel: +65-6748-3488
Fax: +65-6748-1911
Email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8815751
Fax: +971-8-4480051
Email: gmme@emirates.net.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
Email: info@generalmonitors.co.uk