



GENERAL MONITORS

Protection for life.

MODEL DC130

Two-Channel Readout/Relay Module



Features

- Compact Packaging
- Digital Display for Each Channel
- Channel Disable Capable
- Common Relays
- Superior Reliability

Benefits

- Requires less panel or cabinet space
- Provides diagnostic capabilities through visible fault codes
- Can be used as a single-channel module
- Indicates ALARM, WARN & MALFunction Alarms
- Longer product life

Description

The Model DC130 is a two-channel Readout/Relay Module which receives the outputs from two remotely located General Monitors Combustible Intelligent Sensors and processes these signals to provide a digital readout of the gas concentration in "safe" areas. These concentrations are indicated over the range 0-99% LEL (lower explosive limit). When no gas concentration is detected, the digital display for that channel will show a "0" indicating the channel is in normal operation.

Three relays, common to both channels, are provided for the WARN, ALARM and MALFunction circuits. Relay contacts are rated at 4 amp/117 VAC resistive. Setpoints for the ALARM and WARN relays are adjustable through the use of alarm-set potentiometers mounted on the PC board.

Terminations are made at the rear of the instrument through a plug-in connector. These include connections for input power, relay contacts, intelligent sensor power, analog input signal from the intelligent sensor and remote reset for latched alarms.

Provision has been made to inhibit the relays during calibration or alarm setpoint changes. An alarm-inhibit symbol is illuminated when the relays are prevented from operating.

Applications

- Drilling and Production Platforms
- Fuel Loading Facilities
- Compressor Stations
- Oil Well Logging
- LNG/LPG Processing and Storage
- Wastewater Treatment
- Gas Turbines
- Solvent Vapors
- Hydrogen Storage



MODEL DC130

System Specifications

Input Current:	0-20mA from Model S4000C
Display Range:	0-99% LEL, flashing 99 for over-range indication
Repeatability:	±2% full scale
Linearity:	±5% full scale
Front Panel Switches:	Reset
Alarm Disable:	Switch on PC board
Alarm Setting:	Pot adjust
Warning Setting:	Pot adjust
Energized/De-Energized Relay Options:	ALARM and WARN set by DIP switch
Latching/Non-Latching Relay Options:	ALARM and WARN set by DIP switch
Channel Enable:	DIP switch selectable
Reset:	One momentary push-button switch
Remote Reset:	Yes
Electrical Classification:	General purpose, non-hazardous areas
Warranty:	Two years
Approvals:	CSA, FM

Environmental Specifications

Temperature Range:	32°F to 140°F (0°C to 60°C)
Storage Temperature Range:	-31°F to 131°F (-35°C to 55°C)
Humidity:	0-90% non-condensing

Electrical Specifications

Input Power:	105-130 VAC/50-60 Hz 205-255 VAC/50-60 Hz 22-30 VDC 8 watts DC130 plus 250mA max for each S4000C
Channel Input Resistance:	250 ohms maximum
Output Power:	24 VDC nominal at 0.25 amp to each S4000C
Status Indicators:	ALARM, WARNing, MALFunction, CALIBrate, READY, RESET

Mechanical Specifications

Dimensions:	2.1" w x 6.9" h x 11.5" d (53mm x 175mm x 294mm)
Weight:	Approx. 3.8 lb. (1.8kg)
Mounting Configurations:	Panel, Wall & Explosion-proof Enclosures
Standard Configuration:	DC130-1-1-1-2 110VAC, 24VDC, latch alarm, non-latch warn, de-energized

Specifications subject to change without notice.

Represented by:

General Monitors Worldwide



www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California, 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas, 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
email: gmhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road
#09-16 Mactech Building
Singapore 349307
Tel: +65-6748-3488
Fax: +65-6748-1911
email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8815751
Fax: +971-4-8817927
email: gmme@emirates.net.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
email: info@generalmonitors.co.uk