



**GENERAL MONITORS**  
Protection for life.

## FIELD MOUNTED DISPLAY



### Features

- Four-digit Backlit LCD Display
- Loop Powered or +24 VDC
- Software Selectable Settings
- Program Review
- Optional Relays
- Relay Inhibit Mode

### Benefits

- Continuously visible indication of concentration
- Variety of applications
- Ease of operation and enhanced reliability
- Review all option settings
- Application flexibility
- Allows gas checking with outputs disabled



### Description

The General Monitors Field Mounted Display (FMD) is a four-digit backlit LCD readout which provides a display value proportional to sensed current. It is designed for use with General Monitors' Models TS400, TS420, and IR7000.

It is available in an explosion-proof junction box for explosion-proof and general-purpose installations, and in a glass-reinforced polyester junction box for increased safety and general-purpose installations.

For explosion-proof and general purpose installations, the FMD is +24VDC (nominal) powered. Optional relays provide output of warning, alarm and fault conditions at the sensor. Operating mode, display range, warning, and alarm set points are user-selectable via a magnetically activated switch. Relays are user-programmable as latching or non-latching, normally de-energized or normally energized. Latching relays can be reset via a remote reset input or via the magnetic switch.

The display range can be selected via a magnetically activated switch to match the sensor range on the TS400/TS420. The operational mode and gas concentration is displayed on the 4-digit display.

### Operating Modes

#### TS400/TS420

Fault Current	<3.5 mA
Start up	3.6 mA
Calibration	3.75 mA
Operational	4-20 mA
Over-range	>21 mA

#### IR7000

Fault Current	<1.0 mA
Zero/Calibration	1.5 mA
Beam Block	2.0 mA
Operational	4-20 mA
Over-range	>21 mA



# FIELD MOUNTED DISPLAY

The Field Mounted Display (FMD) is a 4 digit LCD display module designed for use with the Models TS400, TS420, and IR7000. The product is available in both the standard explosion-proof (X/P) junction box for explosion-proof and general purpose (GP) installations, and a polyester junction box for increased safety (Exe), and general purpose installations. The following variations are available:

+24VDC Powered	Relays	Classification	Product(s)
Yes	Opt.	X/P, Exe	IR7000
Yes	Opt.	X/P, GP	TS400/TS420
Zero Switch	Opt.	X/P	IR7000
Yes	Opt.	GP, Exe	TS400/TS420

### System Specifications

**Display Ranges:** 1.0, 3.0, 5.0, 10.0, 20.0, 25.0, 50.0, 100, 500, 1000, 2000, 5000

### Electrical

**Classification:** Explosion-proof (XP) Housing: Class I, Div. 1 & 2, Groups B, C, & D; Class II, Div. 1 & 2, Groups E, F, & G; Class III; Class 1, Zone 1 & 2, Group IIB + H2, T6

Polyester Housing: Class I, Zone 0, 1, & 2, Group IIC, T6  
EEx ia/ EExe, IIC, T6

**Warranty:** Two Years

**Approvals:** UL, CUL - GP version only; CSA - XP version only; ATEX & CE Marking

### Environmental Specifications

**Operating Temperature Range:** -40°F to 167°F (-40°C to +75°C)  
*Note: Limited by operating temperature of the attached gas detector.*

**Storage Temperature Range:** -40°F to 185°F (-40°C to +85°C)

**Operating Humidity Range:** 5% to 100% RH, non-condensing

### Electrical Specifications

**Input Power:** 20-36 VDC @ 50 mA max.

**Accuracy:** ±1% of input signal

**Relay Ratings:** 2A @ 30 VDC, 0.5A @125 VAC resistive load max.  
(3X SPDT) - Fault, Warning, and Alarm

**Status Indicators:** Four (4) digit backlit LCD

### Mechanical Specifications

<b>Dimensions:</b>	<b>Explosion-proof Housing</b>	<b>Polyester Housing</b>
	6.4"L x 4.1"W x 3.4"H (161mm x 104mm x 86mm)	4.72"L x 4.72"W x 3.15"H (120mm x 120mm x 80mm)

<b>Weight:</b>	5.6 lbs. (2.5kg)	2.4 lbs. (1.09kg)
----------------	------------------	-------------------

<b>Mounting Holes:</b>	5 inches (127mm) center to center	4.07 inches (103mm) corner to corner
------------------------	--------------------------------------	---

<b>Standard Configuration:</b>	<b>FMD-3-2-1-1-06-1-1</b>	<b>FMD-3-2-1-1-06-1-2</b>
--------------------------------	---------------------------	---------------------------

Specifications subject to change without notice.

Publication #: DS-FMD-E1110

## General Monitors Worldwide



[www.generalmonitors.com](http://www.generalmonitors.com)  
[www.gmitoxics.com](http://www.gmitoxics.com)

### Lake Forest, CA

26776 Simpatica Circle  
Lake Forest, California 92630  
Tel: +1-949-581-4464  
Fax: +1-949-581-1151  
Email: [info@generalmonitors.com](mailto:info@generalmonitors.com)

### Houston, TX

9776 Whithorn Drive  
Houston, Texas 77095  
Tel: +1-281-855-6000  
Fax: +1-281-855-3290  
Email: [gmhou@generalmonitors.com](mailto:gmhou@generalmonitors.com)

### Ireland

Ballybrit Business Park  
Galway  
Republic of Ireland  
Tel: +353-91-751175  
Fax: +353-91-751317  
Email: [info@gmil.ie](mailto:info@gmil.ie)

### Singapore

No. 2 Kallang Pudding Road  
#09-16 Mactech Building  
Singapore 349307  
Tel: +65-6748-3488  
Fax: +65-6748-1911  
Email: [genmon@gmpacifica.com.sg](mailto:genmon@gmpacifica.com.sg)

### United Arab Emirates

P.O. Box 61209  
Jebel Ali  
Dubai  
United Arab Emirates  
Tel: +971-4-8143814  
Fax: +971-4-8857587  
Email: [gmme@generalmonitors.ae](mailto:gmme@generalmonitors.ae)

### United Kingdom

Heather Close  
Lyme Green Business Park  
Macclesfield, Cheshire  
United Kingdom, SK11 0LR  
Tel: +44-1625-619583  
Fax: +44-1625-619098  
Email: [info@generalmonitors.co.uk](mailto:info@generalmonitors.co.uk)