



GENERAL MONITORS
Protection for life.

MODEL 2180A

Single-Channel H₂S Gas Monitor



Features

- Continuous diffusion, solid-state sensor
- High visibility LED status indicators
- Adjustment-free calibration
- Low power consumption—7 watts
- Wide variety of relay options
- Two year warranty

Benefits

- Stable operation over wide ambient temperature and humidity ranges
- Provides visual indication of fault and alarm status at the detector location
- Lower calibration costs
- Lower operating costs
- Provides choice to meet specific customer requirements
- User protection

Description

The Model 2180A is a single-channel system specifically designed for continuous monitoring of Hydrogen Sulfide (H₂S) gas in the ppm (parts-per-million) range. The 2180A controller is a microprocessor-based instrument, which features recent advancements in electronic circuitry and packaging techniques.

User interfaces are provided so that the operator may interpret and direct the Model 2180A in the performance of its various functions. User interfaces consist of a digital display, status indicators, a mode button and a reset button. The digital display provides the user with the gas concentration at the sensor site, fault diagnostic codes, calibration prompts and setup parameters.

The controller should be mounted in a weather protected non-hazardous area. Several GMI accessories are available for panel, wall or 19-inch rack installation. For hazardous areas an explosion proof housing is available for Class I, Division 1, Groups C and D.

Applications

- Compressor Stations
- Drilling Platforms and Rigs
- Gas and Oil Production Platforms
- Fuel Loading Facilities
- Gas Turbines
- LNG Processing and Storage
- Oil Well Logging
- Solvent Vapors
- Wastewater Treatment Plants



MODEL 2180A

System Specifications

Digital Readout: 0-20, 0-50, 0-99 ppm

Accuracy: ±2 ppm or 10% of applied gas, whichever is greater

Electrical Classification: General purpose for mounting in non-hazardous areas, indoors.

Warranty: Two years

Approvals: CSA

Environmental Specifications

Temperature Range: 32°F to 140°F (0°C to 60°C)

Storage Temperature: -4°F to 149°F (-20°C to 65°C)

Humidity: 15-95%, non-condensing

Mechanical Specifications

Mounting: Panel or wall

Dimensions: 2.1" W x 6.9" H x 11.5" D (53mmW x 175mmH x 292mmD)

Weight: 3.8 lbs. (1.8 kg)

Electrical Specifications

Power: 105-130 VAC (205-255 VAC optional), 50-60 Hz, 22-30 VDC, 7 watts nominal (117 VAC)

Output: Analog 4-20mA (300 ohm load max.) Accuracy ±5%, 1.5-20mA

Alarm Circuits: 4A/117 VAC, resistive

Status Indicators: AO - Analog output malfunction
SE - Sensor malfunction
HI - High line voltage
LO - Low line voltage

Standard Configuration: 2180A-1-1-01-1-1 (110 VAC / 24 VDC, latch alarm, non-latch warn, de-energized, 100 ppm standard sensor, 99 ppm meter scale, 1-active channel)

Sensor Specifications

Type: Continuous diffusion, adsorption type

Temperature Range:
Standard Sensor: -65°F to +167°F (-55°C to +75°C)
High Temperature Sensor to +195°F (90°C)
FM Approved: -40°F to +140°F (-40°C to +60°C)

Response Time: T₅₀ < 1 minute with full-scale gas applied (screen)
T₅₀ < 2 minutes with full-scale gas applied (sintered)

Zero Drift: Less than 5% per year

Repeatability: ±2 ppm or 10% of reading, whichever is greater

Life: 3 to 5 years, normal service

Electrical Classification: FM and CSA, Class I, Division 1, Groups B, C and D; ATEX and GOST, Ex ds IIC T6

Specificity: H₂S specific

Warranty: Two years

Cable Length: Four conductor cable. Maximum length of cable between controller and sensor assembly with loop resistance of 20 ohms
NOTE: Shielded cable is recommended

Wire Size AWG	Length	
	(Meters)	(Feet)
14	1,029	3,375
16	686	2,250
18	411	1,350
20	274	900

Specifications subject to change without notice.

Represented by:

General Monitors Worldwide



www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California, 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas, 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
email: gmmhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road
#09-16 Mactech Building
Singapore 349307
Tel: +65-6748-3488
Fax: +65-6748-1911
email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8815751
Fax: +971-4-8817927
email: gmmme@emirates.net.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
email: info@generalmonitors.co.uk