



GENERAL MONITORS
Protection for life.

MODEL TA202A

Single-Channel H₂S Trip Amplifier Module



Features

- RS-485 Serial Communications
- Digital Display
- LED Status Indication
- Relay, Open Collector Alarm & Fault Outputs
- User Setup, Setup Check Modes
- Live Insertable into Rack
- Password Option

Benefits

- Remote set-up and interrogation via General Monitors' Model CC02A Communications module
- Provides visual indication of alarm status and setup cues
- Provides visual indication of fault and status
- Multiple outputs for multi-function use
- Configuration easy to set up or change
- Ease of maintenance
- Tamper-proof operation

Description

The General Monitors Model TA202A is a single-channel H₂S Trip Amplifier Module that has been designed for use with General Monitors' H₂S Intelligent Sensors. It is designed to monitor hydrogen sulfide in parts per million (ppm) levels and provide status indication and alarm outputs.

Microprocessor-based electronics allow all options to be user selectable through front panel interface (mode/select switch and digital display). A digital display on the TA202A indicates fault codes and setup options. Other features of the TA202A are LED indications of status, as well as both open collector and relay outputs for fault, low alarm and high alarm.

Each module has RS-485 serial communications providing an interface with a General Monitors Model CC02A MODBUS communications module. Fault and alarm status, as well as setup options, can be configured via the CC02A module.

The TA202A is part of the Zero Two Series Gas and Fire Detection System which is a flexible solution for various combustible, toxic gas and fire detection applications. All of the Zero Two Series system cards are compatible and can be intermixed within the same rack if required. The Zero Two Series Rack includes options of 4, 8 or 16 channels and provides a bus of common terminals to each channel.

Applications

- Refineries
- Drilling Platforms and Rigs
- Gas Collection and Distribution Facilities
- Gas and Oil Production Platforms
- Mud-logging Operations
- Sulfur Recovery / De-Sulfurization Facilities
- Chemical Plants
- Wastewater Treatment Facilities



MODEL TA202A

System Specifications

Detector Type:	Any General Monitors Metal Oxide Semiconductor (MOS) sensor-based intelligent transmitter
Sensor Life:	3 to 5 years typical
Accuracy:	±2 ppm or 10% of the applied gas, whichever is greater
Response Time:	T50 < 1 minute with full scale gas applied (screen) T50 < 2 minutes with full scale gas applied (sintered)
Measuring Ranges:	0-20 ppm, 0-50 ppm, 0-100 (99) ppm
Front Panel Indicators:	A1 - Warning A2 - Alarm READY - Normal Operation FAULT - Malfunction SETUP - User Options/Check DISPLAY - 2x7 Segment
Test Features:	Power on - Electronic Integrity Card - Functionality & Alarm Ramp LED - Integrity of LED's & Display
Modes:	Setup, Setup Check & Inhibit Outputs
Password:	Prevents unauthorized alteration of setup parameters (can be disabled)
Classification:	<i>TA202A:</i> General purpose, non- hazardous areas <i>Smart Sensor:</i> Explosion-proof
Warranty:	Two years
Approvals:	CSA, CE Marking, Approved for Russia, SIL 2 Suitable.

Environmental Specifications

Operating Temperature Range:	<i>TA202A:</i> 0°F to +150°F (-18°C to +66°C) <i>Smart Sensor:</i> -40°F to +140°F (-40°C to +60°C)
Storage Temperature Range:	<i>TA202A:</i> -40°F to +150°F (-40°C to +66°C) <i>Smart Sensor:</i> -40°F to +140°F (-40°C to +60°C)
Humidity:	5% to 100% RH, non-condensing
EMC Susceptibility:	10V/m max.

Mechanical Specifications

Length:	9.9 inches (251mm)
Height:	6.8 inches (173mm)
Width:	1.0 inch (25mm)
Weight:	11.2 ounces (318 grams)

Electrical Specifications

Power:	20-35 VDC @ 475mA max., including Intelligent Sensor
Input Impedance:	30 ohms
Relay Ratings:	4A @ 250 VAC / 30V RMS/42.4 peak, 3A @ 30 VDC, resistive max. A1, A2 - DPDT Fault - SPDT
Analog Signal:	0 - 20mA (600 ohms max. load @ nominal 24 VDC) Malfunction - 0mA Calib/Setup/Check - 1.5mA 0-100% Scale - 4mA Over-range - 20-22mA
Open Collector Ratings:	100mA @ 35 VDC max. A1, A2, Fault, LA1, LA2, CAL, FUA, UA
Cable Requirements:	3 wire shielded cable. Max. allowable distance between Smart Sensor & TA202A @ 24 VDC nominal: 14AWG - 4500 ft. (1372m) Max. allowable distance for analog output (300 ohms loop resistance max. between AO+ and AO-): 14AWG - 9000 ft. (2740m)
Standard Configuration:	TA202A-2-1-1-1-1-1 Latch alarm, non-latch warn, de-energized, 0-100ppm scale, 3 sec. ramp time

Specifications subject to change without notice.

Represented by:

General Monitors Worldwide



www.generalmonitors.com

Lake Forest, CA

26776 Simpatica Circle
Lake Forest, California, 92630
Tel: +1-949-581-4464
Fax: +1-949-581-1151
email: info@generalmonitors.com

Houston, TX

9776 Whithorn Drive
Houston, Texas, 77095
Tel: +1-281-855-6000
Fax: +1-281-855-3290
email: gmhou@generalmonitors.com

Ireland

Ballybrit Business Park
Galway
Republic of Ireland
Tel: +353-91-751175
Fax: +353-91-751317
email: info@gmil.ie

Singapore

No. 2 Kallang Pudding Road
#09-16 Mactech Building
Singapore 349307
Tel: +65-6748-3488
Fax: +65-6748-1911
email: genmon@gmpacifica.com.sg

United Arab Emirates

P.O. Box 61209
Jebel Ali
Dubai
United Arab Emirates
Tel: +971-4-8815751
Fax: +971-4-8817927
email: gmme@emirates.net.ae

United Kingdom

Heather Close
Lyme Green Business Park
Macclesfield, Cheshire
United Kingdom, SK11 0LR
Tel: +44-1625-619583
Fax: +44-1625-619098
email: info@generalmonitors.co.uk